AMENDMENTS TO THE CLAIMS

1. (Currently amended) A built-in lamp comprising a holder for fastening in an installation surface (11), a bulb (6) and a reflector, with a reflector opening disposed in the direction of illumination defining a generally planar direct light discharge region (1), which is surrounded by a generally coplanar diffuse light discharge region (2) such that scattered light is discharged from the diffuse light discharge region (2) around the direct light discharge region (1), characterized in that

the bulb (6) and the direct light reflector (4) are arranged in a housing (10), said housing having a planar inner surface which overlies the reflector and which forms an additional reflector (7) which reflects at least a portion of light from said bulb to said diffuse light discharge region; and

in that the housing (10) is terminated in at least a largely dust-proof manner by a translucent scattering plate (13, 15) in the region of the diffuse light discharge region (2) and by a plate (13, 14) which is in particular transparent in the region of the direct light discharge region (1) transparent planar plate extending across and covering said direct discharge region and a planar scattering plate extending across and covering said diffuse light discharge region, said transparent planar plate and said planar scattering plate being coplanar with each other, and

wherein the direct light discharge region (1) has a circular shape, and the diffuse light discharge region (2) is bounded on the inner side by a circular line (3) and on the outer side by a polygonal line or by a further circular line.

2. (Original) A built-in lamp in accordance with claim 1, characterized in that the direct light discharge region (1) and the diffuse light discharge region (2) can be acted on by a common bulb (6).

3

- 3. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the reflector opening defining the direct light discharge region (1) is associated with a direct light reflector (4) on whose side remote from the direct light discharge region (1) an additional reflector or background reflector (7) is provided.
- (Previously presented) A built-in lamp in accordance with claim 1, characterized 4. in that a light passage region is formed between the additional reflector (7) and the direct light reflector (4).
- 5. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the diffuse light discharge region (2) can only be acted on indirectly by the bulb (6) via the additional reflector (7).
- 6. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the additional reflector (7) is formed at least partly by at least one planar or predeterminably curved or kinked reflector surface which ensures a pre-determinable splitting of the portion of the reflected light directed to the direct light discharge region (1) and to the diffuse light discharge region (2).

Docket No.: MFA-26002/04

Application No. 10/541,444 Reply to Office Action of February 17, 2009

- 7. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the housing (10) is made to be light-proof and/or dust-proof.

4

- 8. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the additional reflector (7) is made to be specularly reflecting or diffusely reflecting.
- 9. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the direct light reflector (4) is made to be specularly reflecting on its inner side.
- (Previously presented) A built-in lamp in accordance with claim 1, characterized 10. in that the direct light reflector (4) is made to be specularly reflecting on its outer side.
- (Previously presented) A built-in lamp in accordance with claim 1, characterized 11. in that the bulb (6) is located inside the direct light reflector (4) and/or between the direct light reflector (4) and the additional reflector (7).
- 12. (Previously presented) A built-in lamp in accordance with claim 1, characterized in that the translucent scattering plate (13) and the plate (13), which is in particular transparent, are made in one piece.

13. (Canceled)

Docket No.; MFA-26002/04

Application No. 10/541,444

Reply to Office Action of February 17, 2009

14. (Previously presented) A built-in lamp in accordance with claim 1, characterized

5

in that the polygonal line is a rectangular or square line (8).

15. (Previously presented) A built-in lamp in accordance with claim 1, characterized

in that the direct light reflector (4) is held pivotably in the housing (10).

(Previously presented) A built-in lamp in accordance with claim 1, characterized 16.

in that a common inclination of the direct light discharge region (1) with the diffuse light

discharge region (2) is adjustable with respect to the installation surface (11) by a pivoting of the

direct light reflector (4); or

in that an inclination of the direct light discharge region (1) is adjustable with respect to

the diffuse light discharge region (2) by a pivoting of the direct light reflector (4).

(Previously presented) A built-in lamp in accordance with claim 1, characterized 17.

in that the direct light reflector (4) is held pivotably in the housing (10) together with the bulb

(6).

18-20 (Canceled)